



AFS CONNECT MAGNUM MODEL	MAGNUM 180	MAGNUM 200	MAGNUM 220	MAGNUM 240	MAGNUM 250	MAGNUM 280
ENGINE						
Engine Type	Tier 4 B/Final with Selective Catalytic Reduction (SCR)					
HP ISO / ECE R120 (CV)	180 @ rated 2,100 rpm	200 @ rated 2,100 rpm	220 @ rated 2,100 rpm	240 @ rated 2,100 rpm	250 @ rated 2,000 rpm	280 @ rated 2,000 rpm
Maximum Engine HP @ Rated 1,800 rpm ISO / ECE R120 (CV)	200	220	240	260	285	315
Maximum Boosted Engine HP @ Rated 1,800 rpm ISO / ECE R120 (CV)	225	245	260	270	320	350
PTO HP per SAE	155 @ rated 2,100 rpm	170 @ rated 2,100 rpm	185 @ rated 2,100 rpm	205 @ rated 2,100 rpm	205 @ rated 2,000 rpm	235 @ rated 2,000 rpm
Cylinders / Number of Valves / Displacement	6 cyl. / 24 valves/ 6.7 L			6 cyl. / 24 valves/ 8.7 L		
Engine Aspiration	Turbocharger wastegate			Turbocharger eVGT		
Engine Compression Brake	NA			Standard		
ELECTRICAL						
Alternator / Battery	240 amp / 12-volt battery			240 amp / 2 12-volt batteries		
TRANSMISSION/PTO						
PowerDrive: 18 Speed – 25 mph (40 kph)	NA			Optional		
PowerDrive: 19 Speed (Economy) – 25 mph (40 kph)	Standard			NA		
PowerDrive: 19 Speed – 30 mph (50 kph)	Optional			NA		
CVXDrive™ Transmission: 25 mph (40 kph)	Optional			Standard		
CVXDrive Transmission: 30 mph (50 kph)	Optional			Optional		
Rear PTO (Standard / Optional)	540 rpm 1-3/8 in. dia. and 1,000 rpm 1-3/8 in. dia. / NA			1,000 rpm 1-3/4 in. dia. / Optional 3 interchangeable shafts: 540 and 1,000 rpm 1-3/8 in. dia. and 1,000 rpm 1-3/4 in. dia.		
AXLES						
Rear Axle Diameter (Standard / Optional)	4 in. (100 mm) / NA			4.5 in. (115 mm)		
Rear Axle Length (Standard / Optional)	119 in. (3020 mm) / 112 in. (2489 mm)			120 in. (3050 mm) / NA		
Suspended Front Axle	Optional			Optional		
MFD Tread Adjustability	60 – 88 in. (1524 – 2235 mm)			Optional		
MFD Duals	Optional on Class 4.75 axles			Optional		
Wheelbase (PowerDrive / CVXDrive)	118 in. (3000 mm)			120 in. (3050 mm) / 122 in. (3100 mm)		
HYDRAULICS/HITCH						
System Type	Pressure Flow Compensating (PFC)					
Remotes (Standard / Optional)	3 electrohydraulic / 4 or 5 electrohydraulic			4 electrohydraulic / 5 or 6 electrohydraulic		
Main Implement Pump Flow	PowerDrive = 41 gpm (156 L/min.) / CVXDrive = 43 gpm (162 L/min.)			44 gpm (166 L/min.) / 59 gpm (225 L/min.) or 75 gpm (282 L/min.)		
Rear 3-Point Hitch (Standard / Optional)	Cat III/IIIN / NA			Cat III/IIIN / Cat IV/III		
Standard Hitch Lift Capacity	13,600 lb. (6170 kg) without quick coupler; 13,000 lb. (5900 kg) with quick coupler			14,000 lb. (6350 kg)		
Optional Front 3-Point Hitch Lift Capacity	NA			9,426 lb. (4275 kg)		
Front Hitch PTO Speed and Shaft Size	NA			1,000 rpm		
PTO Shaft Size	NA			1 3/8 in. (35 mm) shaft 21 spline		
CAPACITIES						
Fuel Tank	160 gal. (600 L)			PowerDrive: 179 gal. (678 L) / CVXDrive: 163 gal. (617 L)		
Diesel Exhaust Fluid (DEF) Tank	17.5 gal. (66 L)			26 gal. (99 L)		
CAB						
Cab Suspension	Standard					
Volume (Size) / Glass (Area) / Cab Sound Level	109.5 cu ft. (3.1 m³ / 68.5 sq. ft.) / 67 dBa					
WEIGHT						
Average Shipping Weight	21,500 lb. (9750 kg)			28,600 lb. (12973 kg)		

AFS CONNECT MAGNUM MODEL	MAGNUM 310	MAGNUM 340	MAGNUM ROWTRAC™ 340	MAGNUM 380	MAGNUM ROWTRAC 380	MAGNUM 400	MAGNUM ROWTRAC 400
ENGINE							
Engine Type	Tier 4 B/Final with Selective Catalytic Reduction (SCR)						
Engine HP	310 @ rated 2,000 rpm	340 @ rated 2,000 rpm		380 @ rated 2,000 rpm		396 @ rated 2,000 rpm	
Maximum Engine HP @ Rated 1,800 rpm ISO / ECE R120 (CV)	345	375		415		435	
Maximum Boosted Engine HP @ Rated 1,800 rpm ISO / ECE R120 (CV)	380	410		435		NA	
PTO HP per SAE	265 @ rated 2,000 rpm	290 @ rated 2,000 rpm		315 @ rated 2,000 rpm		345 @ rated 2,000 rpm	
Cylinders / Number of Valves / Displacement	6 cyl. / 24 valves / 8.7 L						
Engine Aspiration	Turbocharger eVGT						
Engine Compression Brake	Standard						
ELECTRICAL							
Alternator / Battery	240 amp / 2 12-volt batteries						
TRANSMISSION/ PTO							
PowerDrive: 18 Speed –25 mph (40 kph)	Optional		Standard			NA	
PowerDrive: 19 Speed (Economy) –25 mph (40 kph)	Standard				NA		
PowerDrive: 19 Speed –30 mph (50 kph)	Optional				NA		
PowerDrive: 21 Speed (Economy) –25 mph (40 kph)			NA			Standard	
PowerDrive: 21 Speed (Economy) –30 mph (50 kph)			NA			Optional	NA
CVXDrive Transmission: 25 mph (40 kph)		Optional			Standard		NA
CVXDrive Transmission: 30 mph (50 kph)		Optional	NA	Optional	NA		NA
Rear PTO (Standard / Optional)	1,000 rpm 1-3/4 in. dia. / Optional 3 interchangeable shafts: 540 and 1,000 rpm 1-3/8 in. dia. and 1,000 rpm 1-3/4 in. dia.						
AXLES							
Rear Axle Diameter (Standard / Optional)	4.5 in. (115 mm) / NA		NA	5 in. (127 mm) / NA	NA	5 in. (127 mm) / NA	NA
Rear Axle Length (Standard / Optional)	120 in. (3 050 mm) / NA		NA	120 in. (3 050 mm) / NA	NA	120 in. (3 050 mm) / NA	NA
Suspended Front Axle	Optional						
MFD Tread Adjustability	60 – 88 in. (1 524 – 2 235 mm)						
MFD Duals	Optional						
Wheelbase (PowerDrive / CVXDrive)	120 in. (3 050 mm) / 122 in. (3 100 mm)		124 in. (3 150 mm)		NA / 124 in. (3 150 mm)		124 in. (3 150 mm) / NA
HYDRAULICS / HITCH							
System Type	Pressure Flow Compensating (PFC)						
Remotes (Standard / Optional)	5 electrohydraulic / 6 electrohydraulic						
Main Implement Pump Flow	44 gpm (166 L/min.) / 59 gpm (225 L/min.) or 75 gpm (282 L/min.)						
Rear 3-Point Hitch (Standard / Optional)	Cat III/IIIN / Cat IV/III				Cat IV/III / NA		
Standard Hitch Lift Capacity	15,900 lb. (7 210 kg)		17,500 lb. (7 940 kg)		19,900 lb. (9 026 kg)		19,900 lb. (9 026 kg)
Optional Front 3-Point Hitch Lift Capacity	9,426 lb. (4 275 kg)						
Front Hitch PTO Speed	1,000 rpm						
PTO Shaft Size	1 3/8 in. (35 mm) shaft 21 spline / 1-3/8 in. dia. 6 spline and 1-3/4 in. dia. 20 spline available from parts						
CAPACITIES							
Fuel Tank	PowerDrive: 179 gal. (678 L) / CVXDrive: 163 gal. (617 L)						
Diesel Exhaust Fluid (DEF) Tank	26 gal. (99 L)						
CAB							
Cab Suspension	Standard						
Volume (Size) / Glass (Area) / Cab Sound Level	109.5 cu ft. (3.1 m³ / 68.5 sq. ft.) / 67 dBa						
WEIGHT							
Average Standard Weight	28,800 lb. (13 082 kg)	29,600 lb. (13 458 kg)	36,000 lb. (16 329 kg)	32,200 lb. (14 148 kg)	36,000 lb. (16 329 kg)	32,200 lb. (14 148 kg)	36,000 lb. (16 329 kg)



SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH19082201